

PRODUCT DATA

FAIR-DECOR

DESCRIPTION

Additive for waterborne paints.

MAIN PROPERTIES

Prolongation of drying time of waterborne paints.

RECOMMENDED USES

Decoration of indoor walls in different colour effects.

TECHNICAL DATA

Colour: Colourless
Density: 1.0 g/cm³
Solids Content: In volume: ± 6%
In weight: ± 6%
Flashpoint: Not flammable
VOC-content: Max. 291 g/l

Drying times 20°C/50% r.h.
To touch: Not applicable
To handle: Not applicable
To recoat: After min. 24 hours (mixture base paint / Fair-Décor)
Full hardness: Not applicable

Coverage

Theoretical: 5 - 15 m²/l, depending on the proportion base paint: Fair-Decor
Practical: Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

After the normal preparations, apply the mixture of Fair-Decor / base paint by roller or flat brush on the substrate which contrasts with the colour of the base paint.

APPLICATION CONDITIONS

Apply at a temperature of min. 5°C.

REMARKS

- Mix Fair-Decor with a waterborne base paint in the proportion Fair-Decor / base paint 1 : 1 to 1.5 : 1. The finished product has to be considered as a "decorative effect coating" - VOC cat. A/I; EU Limit values 300 g/l (2007); 200 g/l (2007).
- Treat the wet coat with one of the following techniques: structural roller, sponge, chamois leather, comb, absorbing paper, plastic foil, etc.
- Dependent on the paint and the proportion with which Fair-Decor is mixed, it may be advisable to increase the mechanical resistance by applying a final coat of Divalo varnish and this after full cure of the applied mixture.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info.nl@ro-m.com
www.ro-m.com

N.V. Martin Mathys S.A.

Kolenbergstraat 23
B - 3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)130 400 044
F +33 (0)130 409 980
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Unit 6, Spitfire Close
Coventry Business Park
Coventry, CV5 6UR
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info.uk@ro-m.com
www.ro-m.com

Rust-Oleum Mathys Italia s.r.l.

Largo Donegani 2
20121 Milano, Italia
T +39 335 10 93 482
info.it@ro-m.com
www.ro-m.com